

SAFETY DATA SHEET

Page 1



MR. JANITORIAL SUPPLIES
1125 KERRISDALE BLVD.
NEWMARKET, ON, L3Y 8W1
CANADA
905-836-4250

PRODUCT: CLEAN 3000

SECTION 01: IDENTIFICATION

Supplier identifier..... Mr. Janitorial Supplies
1125 Kerrisdale Blvd.
Newmarket , ON L3Y 8W1
CA
905-836-4250
Product identifier..... CLEAN 3000
Product code..... 344506
Emergency telephone number..... CANUTEC 24-hour number (613-996-6666).
Product use..... HEAVY DUTY CLEANER & DEGREASER FOR OVENS

SECTION 02: HAZARD IDENTIFICATION



Hazard classification..... Skin Irritation — Category 2. Serious Eye Damage — Category 1.
Signal word..... DANGER.
Hazard statement..... H315 Causes skin irritation. H318 Causes serious eye damage.
Precautionary statements..... P264 Wash thoroughly after handling. P280 Wear protective gloves/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash before reuse. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician.

Routes of exposure and acute effects exposure limit: n/a Ld50: n/a lc50: n/a

Inhalation: Breathing high concentration may cause headache, nausea, vomiting, dizziness

Skin: Irritant. Severe irritation and burns on skin. Necrosis of cutaneous tissues

Eyes: Irritant. Extremely corrosive product

Ingestion: Violent pain in throat, mouth, gut, esophagus, and/or stomach perforation, collapse, death

Chronic effects: Prolonged or repeated contacts with skin may cause some irritation, skin dryness, redness, dermatitis from 2-butoxyethanol. There is inadequate evidence in humans for the carcinogenicity of 2-butoxyethanol.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	%	LC50 ppm	LD50mg/kg
2-Butoxyethanol	111-76-2	5-10	450 ppm/4h	1480 mg/kg
Alkyl phenol ethoxylate	9016-45-9	1-5	n/a	2590 mg/kg
Potassium hydroxide	1310-58-3	7-13	2 mg/m3	273 mg/kg
Sodium metasilicate	10213-79-3	0.1-1.0	n/a	n/a

SECTION 04: FIRST-AID MEASURES

Inhalation: Bring person to fresh air. Seek medical attention if discomfort persists.

Skin: Rinse completely with water for at least 15 minutes. Remove soiled clothes and wash before wearing. Seek medical attention should an irritation develop.

Eyes: Immediately flush thoroughly with water for at least 15 minutes, keeping eyelids open. Seek medical attention immediately.

Ingestion: Give plenty of water or milk. Do not induce vomiting. Never give anything to drink to an unconscious person. Seek medical attention immediately.

PRODUCT: CLEAN 3000**SECTION 05: FIRE-FIGHTING MEASURES**

Flash point (tcc, °c): > 93°C lcl: n/a ucl: n/a

Extinguishing media: water, foam, dry chemicals, carbon dioxide

Auto-ignition temperature: n/a

Special fire fighting instructions: A stream of water directed into the product generates a lot of foam

Unusual fire and explosion hazards: None

SECTION 06: ACCIDENTAL RELEASE MEASURES

Stability: stable

Incompatibility: strong oxidizing agents, strong concentrated acids and metallic aluminum, zinc and other soft materials

Hazardous decomposition products: May evolve flammable hydrogen with aluminum

Reactivity: may evolve heat in contact with acids and aluminum

Polymerization: will not occur

Spill, leak or release: Wear personal protective equipment. Stop the leak. Pump the product into drums for disposal, or clean up spills using absorbent material and place in waste container for destruction. Resume cleaning by rinsing with water.

Waste disposal: Dispose according to existing federal, provincial, and municipal regulation.

Personal precautions, protective equipment
and emergency procedures
Environmental precautions.....

Wear protective equipment: goggles, chemically resistant clothing and gloves, and appropriate respirator if in a confined area. Ventilate area if indoor.
Prevent spilled material from entering the ground, water and/or air by using appropriate containment methods. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply. Ventilate the area. Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and
cleaning up

Ensure adequate ventilation. Cover spill area with suitable absorbent material (e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly. Contaminated absorbent material may pose the same hazards as the spilled product. Large Spill: Contain the spilled material. Large spills may be neutralized with dilute alkaline solutions of soda ash or lime.

SECTION 07: HANDLING AND STORAGE

Respiratory protection: Not required under normal applications. Respirator niosh/msha approved if large spill and lack of ventilation or if formation of mists

Ventilation: General ventilation

Protective gloves: Plastic or rubber gloves recommended

Eye protection: Safety goggles recommended

Other protective equipment: Waterproof boots for prolonged contact with spills

Storage and handling conditions: Keep in original tightly closed containers, in a well ventilated room. Keep from freezing.

Prepared by: TECHNICAL DIRECTOR

Telephone #: (905) 836-4250

Preparation date: JANUARY 2022

FOR UPDATES CONTACT: MR. JANITORIAL SUPPLIES
1125 KERRISDALE BLVD.
NEWMARKET, ONTARIO
L3Y 8W1

N/Av = NOT AVAILABLE

N/A = DOES NOT APPLY