

TTB I620 / TTB I620 T



- 16 gallon solution and recovery tanks
- Fully adjustable flow rate from 0.25 gpm to 1 gpm
- (T) 600 watt traction drive motor moves the unit at speeds up to 4.3 m.p.h.
- LED control panel continuously provides the operator with vacuum, water flow, brush pressure and battery information
- Semi parabolic squeegee with Linatex blades pivots from side to side providing excellent water recovery
- The tear away squeegee is equipped with quick release squeegee blades for easy cleaning
- The onboard charger and 2 x 100 amp hour gel batteries provide 2.5 - 3.5 hours of run time
- Low voltage shut off prolongs battery life
- The gel batteries are completely maintenance free, emit 1/40 of the hydrogen gas of wet lead acid batteries, are spill proof and can be charged anywhere
- They are the safest, most dependable and longest life batteries on the market.

Specifications

	TTB I620	TTB I620 T	
Cleaning path	20"	Traction Motor	250 Watts
Pad or Brush Size	20"	Traction Speed	0 - 4.3 mph
Solution / Recovery Tank	16 Gallon	Max Gradient	11 Degrees
Run Time	2.5 - 3.5 Hours	Water Flow Rates	.25 - 1 gpm.
Brush Motor	400 Watt		
Brush Speed	100 rpm		
Vacuum Motor	400 Watt		
Noise Level	65 dBa.		
Batteries	2 x 100 ah gel batteries		
Dimensions	57 x 21 x 43 (LxWxH)		



1205 Britannia Road East,
Mississauga, Ontario, L4W 1C7

1.800.387.3210 TOLL-FREE

1.800.709.2896 FAX

www.nacecare.com